

1990-2002 Mercedes-Benz SL Seat Cover Installation Instructions

For all seat covers

Always wear gloves to protect your hands from any sharp edges under seat and eye protection to protect from elastic straps that may snap back if suddenly released



PDF version of this document
autohq.com/mbsl.aspx



More installation resources
autohq.com/install.aspx

1. Remove backrest cushion from the plastic surround. This is done by folding the seat forward and locating the star screws at the bottom edge of the seat. Remove the star screws on either side of the seat. Bring the seat back to upright position. Pull the backrest out by grabbing the bottom section of the backrest and pulling down and out. Disconnect the power plug.



2. Once you have the backrest out of the vehicle install the top piece of the seat cover. The elastic straps with hooks can be stretched and hooked onto the metal rods.

3. Reinstall the top backrest section. You will notice that the seat fits into two eye holes in the seat surround. Make sure that when you reinstall the backrest that the seat fits properly into the eye holes. This may be a little difficult as the backrest is now thicker. Fold the seat forward and reinstall the star screws (you will need a second person to help with this step in order to squeeze the backrest and the surround together and locate the screw holes).

4. Install the bottom seat cover. Thread the two middle elastic straps through the section of the seat where the top and bottom of the seat meet, towards the back of the car. These elastic straps are going to go under the seat and attach to the D-rings at the front of the seat cushion. As there is very little room under the SL seats, we suggest using a wire coat hanger to pull the straps under the seat. Once you have the seat cover in place, attach the last two outside straps to one another.

Still Need Help?

Call us at (888) 288-6471 x2 for assistance. Video call available through FaceTime, WhatsApp, Skype.

Happy with the results?

We'd love to see a photo! You can text to us at 619-752-4584 or email to sales@autohq.com



We'd appreciate your positive review on Google: